# X5 atom Head





## **Key Facts**

- O Compact Timeless Design: Fits into tight spaces
- O Versatile Zoom: Features a 9:1 range for wide washes or precise breams
- O All-Weather Ready: IP65-rated housing

### **NEXT GENERATION LED WASHLIGHT**

GLP X5 atom IPBig performance, compact form – the GLP X5 Atom delivers unmatched versatility for any project, anywhere.

The GLP X5 atom takes the legacy of the X4 atom to new heights, designed to be as versatile, powerful, and lightweight as possible. This compact fixture seamlessly fits into the tightest spaces while delivering big, dynamic coverage, making it an essential tool across industries – from TV, film, and corporate events to stage design, architecture, and concert touring.

Equipped with high-output RGBL-LEDs, the X5 atom ensures perfectly calibrated, full-spectrum white outputs within its small frame. The powerful 9:1 zoom ratio transitions smoothly from a 34° wash to a tight 3.5° beam, ideal for pinpoint accuracy and stunning mid-air effects, with even color and light intensity distribution.

Ready for all environments, the IP65-rated housing allows year-round indoor or outdoor use. The X5 atom also features a smart interlock system for quick connection, enabling flexible configurations – from singles to grids – while keeping individual control for each head. With compatibility for X4 atom accessories, a removable yoke, and compatibility with industry-standard power infrastructure, the X5 atom streamlines setup and reduces environmental impact.

From one-of-a-kind visuals to effortless adaptability, the GLP X5 atom is your go-to fixture for any project, anywhere.

## Technical Data (1/2)

#### LIGHT SOURCE

Type

	RGBL LED
Power	40 W

#### **OPTICAL SYSTEM**

Total Output	up to 430 lm
Min. Zoom	3.5°
Max. Zoom	32°
Zoom Ratio	1:9

#### **CONTROL & PROGRAMMING**

Protocols	DMX (USITT DMX512-A)   RDM (ANSI/ESTA E1.20)   Art-Net   sACN
Setting and addressing	Control panel with backlit graphic display   4 Button Menu Navigation   DMX   RDM

#### CONNECTIONS

Signal and power

connection Neutrik XLR 4-Pin

## Technical Data (2/2)

#### **ELECTRICAL SPECIFICATIONS**

Power input	26 VDC
Max. Power	40 W

#### THERMAL SPECIFICATIONS

Cooling type	Combined convection and fan forced air
Max. ambient temperature	45 °C / 115 °F
Min. ambient temperature	-10 °C / 14 °F
Thermal protection	Overheating protection

#### **INSTALLATION**

Mounting	Hanging and Florstand Bra- cket   1x foldable Safety Cable attachment point
Orientation	Any
Location	Permanent indoor   Tempora- ry outdoor

#### CONSTRUCTION

Housing color	Black
Material	High-impact flame-resistant thermoplastic   Aluminium   Steel Metal Plates
Protection Rating	IP 65
Construction Features	foldable Floorstand- and Han- ging bracket   4 GLP slide In Connectors

#### **SHIPPING**

Tourpack 6-way

#### **DIMENSIONS & WEIGHT**

Height	177.5 mm / 6.99 in
Diameter	126.5 mm / 4.98 in
Weight netto	2.1 kg / 4.63 lbs

#### **ARTICLE NUMBERS**

X5 atom IP Head	7791
X5 atom IP PSU6	7792

### X5 atom PSU6

#### **INSTALLATION**

Mounting	fix installed Mounting plate (can be installed on back- or topside) screw with 1 pair of 1/4-turn locks and M10 threa- ded hole   2 handle with each 2 times M6 screw threads   2x Safety Cable attachment point Ø13 mm
Orientation	Any
Location	Permanent indoor   Temporary outdoor

#### **ELECTRICAL SPECIFICATIONS**

Power input	100 – 240 V AC / 50 – 60 Hz
Power supply unit	Auto-ranging electronic switch-mode

#### THERMAL SPECIFICATIONS

Temperature range  $-10 \,^{\circ}\text{C} / 14 \,^{\circ}\text{F}$  to  $45 \,^{\circ}\text{C} / 115 \,^{\circ}\text{F}$ 

#### CONSTRUCTION

Housing color	Black
Housing material	High-impact flame-resistant thermoplastic   Aluminium   Steel Metal Plates
Protection Rating	IP 65
Construction Fea- tures	2 Handles   2 position mounting plate

#### CONNECTIONS

Power connection	Neutrik powerCON TRUE1 In/ Out
Signal connection	XLR 5-Pin In/Out   etherCON In/Out (failsafe)
Head connectors	6x XLR 4-Pin female

#### **DIMENSIONS & WEIGHT**

Height	153 mm / 6.02 in
Width	314 mm / 12.4 in
Depth	229.5 mm / 9.04 in
Weight	5.2 kg / 11.46 lbs