

-GLP-



Art.No.: 7678

DCI
IP

JDC2 IP

LIGHT SOURCE

Type	
Strobe Line	White Strobe LED
RGB Plates	RGB LED

Count	
Strobe Line	84
RGB Plates	1,728

OPTICAL SYSTEM

Total Output	
Strobe Line	47,000 lm
RGB Plates	20,000 lm
Strobe and Plates	70,000 lm

Dimension Output	2x 377 x 111 mm /
Lens	2x 14.8 x 4.4 in

MOVEMENT

Tilt	184°, 16 bit
------	--------------

CONTROL & PROGRAMMING

Control Modes	M1: Dual Strobe (CH24 / 21 Fixture) M2: Segment 1-1 (CH46 / 11 Fixture) M3: Segment 12-12 (CH91 / 5 Fixture) M4: Segment 12-24 (CH127 / 4 Fixture; DEFAULT) M5: JDC1 Spix Patch (CH68 / 7 Fixture)
---------------	--

Protocols	DMX (USITT DMX512-A) RDM (ANSI/ESTA E1.20) ArtNet / sACN (in development) LumenRadio CRMX (optional) iQ.Mesh
-----------	--

ELECTRICAL SPECIFICATIONS

Max. Power	1,500 W
------------	---------

CONSTRUCTION

Protection Rating	IP 65
-------------------	-------

DIMENSIONS & WEIGHT

Height head straight up	354 mm / 13.94 in
-------------------------	-------------------

Height head vertical	452 mm / 17.8 in
----------------------	------------------

Width across yoke	444 mm / 17.48 in
-------------------	-------------------

Depth head vertical	230 mm / 17.48 in
---------------------	-------------------

Weight netto	23.5 kg / 51.8 lbs
--------------	--------------------

